

# MATERIAL SAFETY DATA SHEET

## GENERAL INFORMATION

PRODUCT NAME OR NUMBER (as it appears on label) Aqua-Gel® II Utility Cable Pulling Lubricant	CATALOG NUMBER All "31" Series
MANUFACTURER'S NAME <b>IDEAL INDUSTRIES, INC.</b>	EMERGENCY TELEPHONE NO. <b>(815) 895-5181</b>
ADDRESS (Number, Street, City, State, Zip Code) <b>Becker Place, Sycamore, IL 60178</b>	
HAZARDOUS MATERIAL DESCRIPTION, PROPER SHIPPING NAME, HAZARD CLASS, HAZARD CLASS, HAZARD ID NO. (49 CFR 172.101) None	
CHEMICAL DESCRIPTION Polymer-based Mixture	FORMULA Proprietary

### SECTION I - INGREDIENTS

CAS REGISTRY NO.	%W	CHEMICAL NAME(S)*	Listed as a carcinogen in NTP, IARC or OSHA 1910(z) (specify)
7732-18-5	<90	Water	No
9038-95-3	<10	Oxirane, Methyl-, Polymer With Oxirane, Monobutyl Ether	No
9003-11-6	<5	Polyoxypropylene-polyoxyethylene Block Copolymer	No
102-71-6, 7732-18-5, 10246-68-1, 22919-56-8, 64665-57-2, 693-23-2	<1	Proprietary Mixture of Ethanol, 2,2',2" Nitrilotris; Water; Nonanoic acid; Triethanolamine salt, Caprylic acid; triethanolamine salt; 1H-Benzotriazole, 4-methyl-,sodium salt; Dodecanedioic acid	No
1310-58-3	<2	20% Potassium Hydroxide	No
52-51-7	<0.1	2-Bromo-2-Nitropropane 1,3 Diol	No
3844-45-9 7757-82-6 7647-14-5	<0.1	Blue Pigment	No

### SECTION II - PHYSICAL DATA

BOILING POINT 212 °F    100 °C	SPECIFIC GRAVITY (H <sub>2</sub> O=1) 0.98	PERCENT VOLATILE BY VOLUME (%) <90
SOLUBILITY IN WATER Infinite	pH = 7.0 - 8.0	PERCENT SOLID BY WEIGHT (%) ~10
APPEARANCE AND ODOR Clear blue gel, mild odor	IS MATERIAL: LIQUID    SOLID (GEL)    GAS    PASTE	

### SECTION III - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT    None    method used    C.O.C	FLAMMABLE LIMITS	LEL	UEL
		None	None
EXTINGUISHING MEDIA Use extinguishing media suitable for surrounding materials.			
SPECIAL FIRE FIGHTING PROCEDURES None			
UNUSUAL FIRE AND EXPLOSION HAZARDS None			

\* None of the chemical raw materials contained in this formulation are considered hazardous under the Federal Hazards Communication Standard 29 C. F. R 1910.1200

**SECTION IV - HEALTH HAZARD INFORMATION**

EFFECTS OF OVEREXPOSURE - Conditions to Avoid	None normally expected. Upon prolonged contact, may cause temporary eye discomfort.
THRESHOLD LIMIT VALUE	N.E.
PRIMARY ROUTES OF ENTRY Inhalation <input type="checkbox"/> Skin Contact <input checked="" type="checkbox"/> Other (specify)	
EMERGENCY FIRST AID PROCEDURES	
SKIN CONTACT:	Wash with soap and water.
EYE CONTACT:	Flush with water.
INGESTION:	Do not induce vomiting. Consult physician or local poison control center.

**SECTION V - REACTIVITY DATA**

STABILITY	UNSTABLE		CONDITIONS TO AVOID
	STABLE	X	Avoid prolonged storage at temperatures exceeding 190 F.
INCOMPATIBILITY (materials to avoid)			
Avoid strong oxidizers and nitrites.			
HAZARDOUS DECOMPOSITION PRODUCTS:			
In the unlikely event of combustion of dried residue, oxides and nitrogen may be released.			
HAZARDOUS POLYMERIZATION	MAY OCCUR		CONDITIONS TO AVOID
	WILL NOT OCCUR	X	None

**SECTION VI - SPILL AND LEAK PROCEDURES**

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED	Wipe up, shovel or vacuum spilled material. Clean up spills immediately as they can be dangerously slippery.
WASTE DISPOSAL METHOD	Comply with Federal, state and local regulations for solid landfill.
CERCLA (Superfund) REPORTABLE QUANTITY (in lbs)	N/A
RCRA HAZARDOUS WASTE NO. (40CFR 261.33)	N/A
VOLATILE ORGANIC COMPOUND (VOC) (as packaged, minus water)	1.7 gms / ltr
<sup>3</sup> Theoretical ____ lb/gal	N/A
<sup>3</sup> Analytical ____ lb/gal	N/A

**SECTION VII - PERSONAL PROTECTION INFORMATION**

RESPIRATORY PROTECTION (specify type)			
None normally required.			
VENTILATION	LOCAL EXHAUST (Specify Rate)	None	SPECIAL None
	MECHANICAL (General) (Specify Rate)	Recommended in closed areas.	OTHER None
PROTECTIVE GLOVES (specify type)	EYE PROTECTION (specify type)		
None normally needed -Neoprene if necessary	None normally required. Safely glasses or splash goggles recommended.		
OTHER PROTECTIVE EQUIPMENT			
Eye fountain in work area is recommended but not necessary.			

**SECTION VIII - SPECIAL PRECAUTIONS**


PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING	Store at temperatures between 40 - 180 F. Avoid freezing.
OTHER PRECAUTIONS	Keep away from children, infants and pets.

**SECTION IX - ADDITIONAL INFORMATION**

Extreme temperatures of combustion or burning and contact with nitrites could result in the formation of nitrosamines which are potential carcinogens. This condition is unlikely to occur.

N/A = Not Applicable, N.E. = None Established

THIS MATERIAL SAFETY DATA SHEET PREPARED BY:

NAME	James R. MacMurdo	SIGNATURE  
TITLE	Mgr., Construction Market Development	
DATE	01/11/2011	