



**Revision Number:** 001.1

**Issue date:** 09/09/2011

**1. PRODUCT AND COMPANY IDENTIFICATION**

**Product name:** Loctite® PL® Premium Polyurethane Construction Adhesive **IDH number:** 1390595  
**Product type:** 1-component-polyurethane adhesive **Region:** United States  
**Company address:** Henkel Corporation, One Henkel Way, Rocky Hill, Connecticut 06067  
**Contact information:** Telephone: 800.624.7767  
 MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711  
 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

**2. HAZARDS IDENTIFICATION**

**EMERGENCY OVERVIEW**

|                        |                    |                             |                    |
|------------------------|--------------------|-----------------------------|--------------------|
| <b>Physical state:</b> | high viscosity     | <b>HMIS:</b>                |                    |
| <b>Color:</b>          | Beige              | <b>HEALTH:</b>              | *2                 |
| <b>Odor:</b>           | like vegetable oil | <b>FLAMMABILITY:</b>        | 1                  |
|                        |                    | <b>PHYSICAL HAZARD:</b>     | 1                  |
|                        |                    | <b>Personal Protection:</b> | See MSDS Section 8 |

**WARNING:** HARMFUL IF INHALED.  
 CAUSES EYE, SKIN AND RESPIRATORY TRACT IRRITATION.  
 MAY CAUSE ALLERGIC SKIN AND RESPIRATORY REACTION.

**Relevant routes of exposure:** Inhalation, Skin, Eyes, Ingestion

**Potential Health Effects**

**Inhalation:** As a result of previous repeated overexposures or a single large dose, certain individuals will develop isocyanate sensitization (chemical asthma) which will cause them to react to a later exposure to isocyanate at levels well below the TLV. Chronic overexposure to isocyanates has been reported to cause lung damage. Dryness of nasal passages, sore throat, cough, tightness of chest, shortness of breath. Persons suffering from allergic reactions to isocyanates should avoid contact with the product. This product may cause sensitization by inhalation and skin contact. May cause respiratory tract irritation.

**Skin contact:** Contact with skin can cause irritation and allergic reaction (sensitization) in some individuals. This product may discolor the skin.

**Eye contact:** Contact with eyes will cause irritation.

**Ingestion:** Ingestion of this product may cause nausea, vomiting and diarrhea.

**Existing conditions aggravated by exposure:** Development of preexisting skin or lung allergy symptoms may increase. Asthma.

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

**See Section 11 for additional toxicological information.**

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

| Hazardous components                                 | CAS NUMBER | %       |
|--|------------|---------|
| Talc   | 14807-96-6 | 30 - 60 |
| Methylenebis(phenylisocyanate)                       | 101-68-8   | 10 - 30 |
| Hydrocarbon C11-25 dearomatized                      | 64742-46-7 | 10 - 30 |
| Methylene bisphenyl isocyanate                       | 26447-40-5 | 1 - 5   |
| Diphenylmethane-diisocyanate, isomers and homologues | 9016-87-9  | 1 - 5   |
| Quartz (SiO <sub>2</sub> )                           | 14808-60-7 | 0.1 - 1 |

### 4. FIRST AID MEASURES

|                            |  |
|----------------------------|--|
| <b>Inhalation:</b>         | If inhaled, immediately remove the affected person to fresh air. Immediate medical treatment necessary.  |
| <b>Skin contact:</b>       | Wash affected area immediately with soap and water. If symptoms develop and persist, get medical attention. Remove contaminated clothes.   |
| <b>Eye contact:</b>        | In case of contact with the eyes, rinse immediately with plenty of water for 15 minutes, and seek immediate medical attention.   |
| <b>Ingestion:</b>          | Do not induce vomiting. Rinse the mouth. Drink plenty of water. Immediate medical advice necessary.  |
| <b>Notes to physician:</b> | An individual having a dermal or pulmonary sensitization reaction to this material should be removed from further exposure to any diisocyanate. Treatment based on judgement of the physician in response to reactions of the patient. |

### 5. FIRE FIGHTING MEASURES

|  |  |
|--|--|
| <b>Flash point:</b>                        | > 200 °F (> 93.33 °C) no method  |
| <b>Autoignition temperature:</b>           | No information available.  |
| <b>Flammable/Explosive limits - lower:</b> | 1.6 %  |
| <b>Flammable/Explosive limits - upper:</b> | 10.2 %   |
| <b>Extinguishing media:</b>                | Water fog. Foam Carbon dioxide.  |
| <b>Special firefighting procedures:</b>    | Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear. In case of fire, keep containers cool with water spray. |
| <b>Unusual fire or explosion hazards:</b>  | None known   |
| <b>Hazardous combustion products:</b>      | Nitrous gases Irritating fumes. Isocyanate vapors.   |

### 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

|                                   |  |
|-----------------------------------|--|
| <b>Environmental precautions:</b> | Do not empty into drains / surface water / ground water.   |
| <b>Clean-up methods:</b>          | Ensure adequate ventilation. Scrape up spilled material and place in a closed container for disposal. Wear suitable protective clothing, gloves and eye/face protection. |

## 7. HANDLING AND STORAGE

|                  |   |
|------------------|---|
| <b>Handling:</b> | Avoid contact with eyes, skin and clothing. Avoid extreme temperatures. Exposure to vapors of heated MDI can be extremely dangerous. Wash thoroughly after handling. Protect from moisture. Use only with adequate ventilation. |
| <b>Storage:</b>  | For safe storage, store between 18.3 °C (64.9 °F) and 40 °C (104°F) Avoid moisture. Keep in a cool, well ventilated area away from heat, sparks and open flame. Keep container tightly closed until ready for use.              |

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

| Hazardous components                                 | ACGIH TLV   | OSHA PEL   | AIHA WEEL | OTHER  |
|--|---|--|-----------|--------|
| Talc   | 2 mg/m <sup>3</sup> TWA<br>Respirable fraction.     | 20 MPPCF TWA<br>2.4 MPPCF TWA<br>Respirable.<br>0.1 mg/m <sup>3</sup> TWA<br>Respirable.<br>0.3 mg/m <sup>3</sup> TWA<br>Total dust. | None      | 50 ppm |
| Methylenebis(phenylisocyanate)                       | 0.005 ppm TWA                                       | 0.02 ppm (0.2 mg/m <sup>3</sup> ) Ceiling  | None      | None   |
| Hydrocarbon C11-25 dearomatized                      | 5 mg/m <sup>3</sup> TWA<br>Inhalable fraction.      | 5 mg/m <sup>3</sup> TWA<br>Mist.   | None      | None   |
| Methylene bisphenyl isocyanate                       | None  | None   | None      | None   |
| Diphenylmethane-diisocyanate, isomers and homologues | 0.005 ppm TWA                                       | 0.02 ppm (0.2 mg/m <sup>3</sup> ) Ceiling  | None      | None   |
| Quartz (SiO <sub>2</sub> )                           | 0.025 mg/m <sup>3</sup> TWA<br>Respirable fraction. | 2.4 MPPCF TWA<br>Respirable.<br>0.1 mg/m <sup>3</sup> TWA<br>Respirable.<br>0.3 mg/m <sup>3</sup> TWA<br>Total dust.                 | None      | None   |

|                                |  |
|--------------------------------|--|
| <b>Engineering controls:</b>   | Local exhaust ventilation is recommended when general ventilation is not sufficient to control airborne contamination below occupational exposure limits.  |
| <b>Respiratory protection:</b> | Observe OSHA regulations for respiratory use (29 CFR 1910.134). Use a NIOSH approved air-purifying respirator if the potential to exceed established exposure limits exists. Respirator with combination filter for vapor/particulate. However, due to the poor warning properties of MDI, proper fit and timely replacement of filter elements must be ensured. |
| <b>Eye/face protection:</b>    | Safety glasses with side-shields. Full face protection should be used if the potential for splashing or spraying of product exists.  |
| <b>Skin protection:</b>        | Suitable protective clothing   |

## 9. PHYSICAL AND CHEMICAL PROPERTIES

|                              |   |
|------------------------------|---|
| <b>Physical state:</b>       | high viscosity                            |
| <b>Color:</b>                | Beige                                     |
| <b>Odor:</b>                 | like vegetable oil                        |
| <b>Odor threshold:</b>       | Not available.                            |
| <b>pH:</b>                   | Neutral                                   |
| <b>Vapor pressure:</b>       | Not available.                            |
| <b>Boiling point/range:</b>  | 172 - 341 °C (341.6 - 645.8 °F) no method |
| <b>Melting point/ range:</b> | Not applicable                            |

**Specific gravity:** 1.2600  
**Vapor density:** Heavier than air  
**Flash point:** > 200 °F (> 93.33 °C) no method  
**Flammable/Explosive limits - lower:** 1.6 %  
**Flammable/Explosive limits - upper:** 10.2 %  
**Autoignition temperature:** No information available.  
**Evaporation rate:** Not available.  
**Solubility in water:** Slightly soluble  
**Partition coefficient (n-octanol/water):** Not available.  
**VOC content:** 3.5 %; 45 g/l

## 10. STABILITY AND REACTIVITY

**Stability:** Stable under normal conditions of storage and use.  
**Hazardous reactions:** Contact with moisture, other materials that react with isocyanates, or temperatures above 350° F (177° C), may cause polymerization.  
**Hazardous decomposition products:** Irritating and/or toxic fumes and gases may be emitted upon the product's decomposition. nitrogen oxides Aromatic isocyanates. carbon oxides.  
**Incompatible materials:** Oxidizing agents. Alcohols. Water.  
**Conditions to avoid:** Avoid moisture. Keep away from open flames, hot surfaces and sources of ignition. Prolonged exposure to heat.

## 11. TOXICOLOGICAL INFORMATION

| Hazardous components                                 | NTP Carcinogen    | IARC Carcinogen | OSHA Carcinogen<br>(Specifically Regulated) |
|--|-------------------|-----------------|---|
| Talc   | No                | No              | No  |
| Methylenebis(phenylisocyanate)                       | No                | No              | No  |
| Hydrocarbon C11-25 dearomatized                      | No                | No              | No  |
| Methylene bisphenyl isocyanate                       | No                | No              | No  |
| Diphenylmethane-diisocyanate, isomers and homologues | No                | No              | No  |
| Quartz (SiO2)  | Known carcinogen. | Group 1         | No  |

| Hazardous components                                 | Health Effects/Target Organs                          |
|--|---|
| Talc   | Irritant, Lung, Some evidence of carcinogenicity      |
| Methylenebis(phenylisocyanate)                       | Irritant, Respiratory, Allergen                       |
| Hydrocarbon C11-25 dearomatized                      | Irritant  |
| Methylene bisphenyl isocyanate                       | Allergen, Irritant, Mutagen, Respiratory              |
| Diphenylmethane-diisocyanate, isomers and homologues | Allergen, Irritant, Kidney, Liver, Respiratory        |
| Quartz (SiO2)  | Immune system, Lung, Some evidence of carcinogenicity |

## 12. ECOLOGICAL INFORMATION

**Ecological information:** Not available.

### 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

|  |  |
|--|--|
| <b>Recommended method of disposal:</b> | Dispose of according to Federal, State and local governmental regulations.   |
| <b>Hazardous waste number:</b>         | It is the responsibility of the user to determine if an item is hazardous as defined in the Resource Conservation and Recovery Act (RCRA) at the time of disposal. Product uses, transformations, mixtures, processes, etc., may render the resulting material hazardous, under the criteria of ignitability, corrosivity, reactivity and toxicity characteristics of the Toxicity Characteristics Leaching Procedure (TCLP) 40 CFR 261.20-24. |

### 14. TRANSPORT INFORMATION

#### U.S. Department of Transportation Ground (49 CFR)

|                                  |               |
|----------------------------------|---------------|
| <b>Proper shipping name:</b>     | Not regulated |
| <b>Hazard class or division:</b> | None          |
| <b>Identification number:</b>    | None          |
| <b>Packing group:</b>            | None          |

#### International Air Transportation (ICAO/IATA)

|                                  |               |
|----------------------------------|---------------|
| <b>Proper shipping name:</b>     | Not regulated |
| <b>Hazard class or division:</b> | None          |
| <b>Identification number:</b>    | None          |
| <b>Packing group:</b>            | None          |

#### Water Transportation (IMO/IMDG)

|                                  |               |
|----------------------------------|---------------|
| <b>Proper shipping name:</b>     | Not regulated |
| <b>Hazard class or division:</b> | None          |
| <b>Identification number:</b>    | None          |
| <b>Packing group:</b>            | None          |

### 15. REGULATORY INFORMATION

#### United States Regulatory Information

|  |   |
|--|---|
| <b>TSCA 8 (b) Inventory Status:</b>    | All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.   |
| <b>TSCA 12(b) Export Notification:</b> | None above reporting de minimus   |
| <b>CERCLA/SARA Section 302 EHS:</b>    | None above reporting de minimus   |
| <b>CERCLA/SARA Section 311/312:</b>    | Immediate Health, Delayed Health  |
| <b>CERCLA/SARA 313:</b>                | This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Methylenebis(phenylisocyanate) (CAS# 101-68-8). Diphenylmethane-diisocyanate, isomers and homologues (CAS# 9016-87-9). |
| <b>California Proposition 65:</b>      | This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known in the State of California to cause cancer.   |

#### Canada Regulatory Information

|                              |   |
|------------------------------|---|
| <b>CEPA DSL/NDSL Status:</b> | Contains one or more components listed on the Non-Domestic Substances List. All other components are listed on or are exempt from listing on the Domestic Substances List. Components listed on the NDSL must be tracked by all Canadian Importers of Record as required by Environment Canada. They may be imported into Canada in limited quantities. Please contact Regulatory Affairs for additional details. |
|------------------------------|---|

### 16. OTHER INFORMATION

**This material safety data sheet contains changes from the previous version in sections:** This Material Safety Data Sheet contains changes from the previous version in Section(s): 1, 3, 15

**Prepared by:** Mary Ellen Roddy, Sr. Regulatory Affairs Specialist

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation does not assume responsibility for any results obtained by persons over whose methods Henkel Corporation has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Corporation's products. In light of the foregoing, Henkel Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation further disclaims any liability for consequential or incidental damages of any kind, including lost profits.