



Chemical Name: PAG 150

Manufacturer: Napa Professional AC Parts

Container size: 8oz.

Location: VLA

Disposal: Place empty container in trash.

SUPERCOOL PAG 46, 100, 150

MATERIAL SAFETY DATA SHEET

Emergency Phone Number: 561-582-2245

Date: May 15, 2000

SECTION 1

Company Name:
Address:
Phone/Fax:
Trade Name:
Chemical Name:
Chemical Family:
Formula:
CAS#:
Applications:

COMPANY IDENTIFICATION AND CHEMICAL PRODUCT

TSI, Inc.
932 South Dixie Highway, Lake Worth, Florida 33460
561-582-2245 / 561-582-1499
PAG Refrigeration Compressor Lubricant.
Synthetic Polyalkylene glycol hydrocarbon mixture
Synthetic Polyalkylene glycol hydrocarbon mixture
Proprietary
Proprietary
PAG Refrigeration Compressor Lubricant is used as a fluid in HFC and other refrigeration systems.

SECTION 2

General:
FDA Statement:

COMPOSITION / INFORMATION ON INGREDIENTS

This Product contains No Known Carcinogens. No Special Warning Labels Are Required Under OSHA 29 CFR 1910.1200.
N/A

SECTION 3

Appearance:
Known Hazards:

HAZARDS IDENTIFICATION

Clear liquid, orange tint.
This product does not require any special warning labels under OSHA 29 CFR 1910.1200 and contains no hazardous ingredients. Product is slight Eye and Skin irritant.

SECTION 4

Eyes:
Skin:
Inhalation:
Ingestion:

FIRST AID MEASURES

Flush with clean, lukewarm water (low pressure) occasionally lifting eyelids. Physician assessment if eyes are inflamed.
Wash affected areas thoroughly with soap and water. Wash contaminated clothing before reuse.
Avoid breathing oil mists. Remove to fresh air. Give artificial respiration if not breathing. Oxygen may be given by qualified personnel if breathing is difficult. Get medical attention.
Do not induce vomiting. Force fluids. Has laxative effect.

SECTION 5

Flash Point:
Flammable Limits:
Auto Ignition Temp:
Fire & Explosion Hazards:
Extinguishing Media:
Fire Fighting Procedures:

FIRE FIGHTING MEASURES

440°F min
N/A
N/A
LOW FIRE HAZARD - Do not cut, drill, or weld empty containers.
Dry chemical foam, water spray, carbon dioxide for small fires.
Contain liquid, cover with extinguishing agent, use water spray to cool fire exposed containers and as protective screen. Do not point solid water stream directly into burning fluid to avoid spreading.

SECTION 6

Spill or Leak:
Waste Disposal:

ACCIDENTAL RELEASE MEASURES

Contain Spill, absorb with inert absorbent such as dry clay, sand, diatomaceous earth, commercial sorbents or recover using pumps. Scoop up used absorbents into approved receptacles.
Dispose in approved, secure landfill site or through a licensed waste reclaimer.

SECTION 7

Storage Temp - min / max:

Shelf Life:

Precautions:

SECTION 8

Eye Protection:

Skin Protection:

Respiratory Protection:

Ventilation:

Exposure Limits:

SECTION 9

Appearance:

Boiling Point:

Vapor Pressure:

Specific Gravity:

Volatiles, % Volume:

Odor:

Solubility in Water:

Evaporation Rate:

Viscosity:

SECTION 10

Stability:

Hazardous Polymerization:

Incompatibilities:

Decomposition Products:

SECTION 11

General:

SECTION 12

General:

SECTION 13

Waste Disposal:

SECTION 14

Technical Name:

D.O.T. Hazard Class:

U.N. / N.A. #:

Product Label:

SECTION 15

OSHA STATUS:

TSCA STATUS:

RCRA STATUS:

SECTION 16

General:

HANDLING AND STORAGE

None / 104°F recommended

Indefinite in original container

Not for internal use. Avoid contact with skin, eyes, clothing.

EXPOSURE CONTROL / PERSONAL PROTECTION

Chemical Goggles if splashing is likely or high pressure systems are used.

For direct contact of more than 2 hours, PVC or Nitrile gloves are recommended.

Normally not necessary. If mist is generated, wear approved organic respirator suitable for oil mist areas with sufficient oxygen.

General ventilation.

Acute LD₅₀ > 2000 mg/Kg (rat : oral)

PHYSICAL AND CHEMICAL PROPERTIES

Clear liquid, orange tint.

>200°C

<0.001 kPa @ 25°C

0.85-.097

0%

Characteristic odor

Slight

Nil

@40°C Varies depending on grade

REACTIVITY

Product is STABLE

Will not occur.

Strong oxidizers.

Analogous compounds evolve, carbon monoxide, carbon dioxide, and other undefined fragments when burned.

TOXICOLOGICAL INFORMATION

Acute LD₅₀ > 2000 mg/Kg (rat : oral)

ECOLOGICAL INFORMATION

Biodegradable CEC L33A93 > 80% @ 45 Days.

DISPOSAL CONSIDERATIONS

Used product must be disposed of in accordance with Federal, State, and Local environmental control regulations. Incineration is preferred. DO NOT HEAT OR CUT EMPTY CONTAINERS WITH ELECTRIC OR GAS TORCH.

TRANSPORTATION INFORMATION

Synthetic Polyalkylene glycol hydrocarbon mixture

NR

NR

PAG Refrigeration Compressor Lubricant

REGULATORY INFORMATION

Non-Hazardous under 29 CFR 1910.1200

N/A

If discarded in its purchased form this product would not be a hazardous waste either by listing or characteristic. However, it is the responsibility of the product user to determine at the time of disposal, whether the material being disposed of is a hazardous waste (40 CFR 261.20-24).

OTHER INFORMATION

This information is furnished without warranty, expressed or implied, except that is accurate to the best knowledge of TSI, Inc. The data on this sheet related only to the specific material designed herein. TSI, Inc. assumes no legal responsibility for the use or reliance upon these data.