

MATERIAL SAFETY DATA SHEET

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: SUPCO 88 Oil Additive

PART NUMBER:

GENERAL USE: Oil additive

PRODUCT DESCRIPTION: Colorless to slightly tinted liquid, characteristic hydrocarbon odor.



MANUFACTURER'S NAME

Sealed Unit Parts Co., Inc.

DATE PREPARED: May 25, 2005

SUPERSEDES: August 18, 1998

Page 1 of 4

ADDRESS (NUMBER, STREET, P.O. BOX)

2230 Landmark Place

TELEPHONE NUMBER FOR INFORMATION

(732) 223-6644

(CITY, STATE AND ZIP CODE)

Allenwood, NJ 08720

COUNTRY

USA

EMERGENCY TELEPHONE NUMBER

(732) 223-6644

DISTRIBUTOR'S NAME

Same

ADDRESS (NUMBER, STREET, P.O. BOX)

TELEPHONE NUMBER FOR INFORMATION

(CITY, STATE AND ZIP CODE)

COUNTRY

EMERGENCY TELEPHONE NUMBER

SECTION 2 - HAZARDOUS INGREDIENTS

HAZARDOUS COMPONENTS	% (by weight)	CAS #	EINECS #	Hazard Symbol	RISK PHRASES Full Text Section 16
Kerosene (petroleum), hydrosulfurized	30 - 60	64742-81-0	265-184-9	Xn	R-10, 65
Petroleum distillate, hydrotreated heavy paraffinic	15 - 40	64742-53-6	265-156-6	Xn	R-65, 66, 67
Petroleum distillate, hydrotreated heavy paraffinic	10 - 30	64742-52-5	265-155-0	Xn	R-65, 66, 67
Benzyl disulfide	0.5 - 1.0	150-60-7	205-764-0	Xi	R-43

SECTION 3 - HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Colorless combustible liquid, potentially hazardous vapors. Can cause serious or fatal complications if swallowed. Can cause eye and skin irritation upon contact. Inhalation of vapors can cause anesthetic effect leading to death in poorly ventilated areas. Hazard Symbols for this product - Xn Risk Phrases - R 10, 65, 66, 67

POTENTIAL HEALTH EFFECTS

INHALATION: Inhalation of vapors can cause anesthetic effect leading to death in poorly ventilated areas. High concentrations of mist may be irritating to the respiratory tract.

SKIN: No significant irritation is expected to occur upon short-term exposure.; prolonged contact may cause moderate irritation.

EYES: Minimal irritation and discomfort may result from short-term contact with liquid, mist, and/or vapor.

INGESTION: Non-toxic; may cause gastric distress, vomiting and diarrhea. DO NOT induce vomiting. Aspiration of vomitus into the lungs must be avoided; minute amounts aspirated into the lungs can produce severe lung injury or death.

CARCINOGENICITY

NTP?

No

IARC MONOGRAPHS?

No

OSHA REGULATED?

No

MATERIAL SAFETY DATA SHEETPRODUCT NAME: SUPCO 88 Oil Additive
May 25, 2005

Page 2 of 4

SECTION 4 - FIRST AID MEASURES

INHALATION: Remove affected person to fresh air; provide oxygen if breathing is difficult; if affected person is not breathing, administer CPR and seek emergency medical attention.

SKIN: Remove contaminated clothing; wash affected area with soap and water; launder contaminated clothing before reuse; if irritation persists, seek medical attention.

EYES: Check for and remove contact lenses. Flush eyes with clear running water for 15 minutes while holding eyelids open; if irritation persists, seek medical attention.

INGESTION: DO NOT induce vomiting; if vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into lungs; seek immediate medical attention. Small amounts entering mouth should be rinsed out until taste is gone.

SECTION 5 - FIRE FIGHTING MEASURES

GENERAL HAZARDS: Product is flammable. Products of combustion include compounds of carbon, hydrogen and oxygen, including carbon monoxide and small amounts of sulfur.

EXTINGUISHING MEDIA

Carbon dioxide, water fog, dry chemical, chemical foam.

FIRE FIGHTING PROCEDURES

Firefighters must wear full facepiece self - contained breathing apparatus in positive pressure mode. Do not use solid stream of water since stream will scatter and spread fire. Fine water spray can be used to keep fire - exposed containers cool.

UNUSUAL FIRE AND EXPLOSION HAZARDS

Closed containers can explode due to buildup of pressure when exposed to extreme heat. Do not use direct stream of water on pool fires as product may reignite on water surface. Caution - Material is flammable!

HAZARDOUS COMBUSTION PRODUCTS

Smoke, fumes or vapors, oxides of carbon, small amounts of sulfur.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: CAUTION - FLAMMABLE - Evacuate and ventilate area; remove all sources of sparks, ignition and open flames; confine and absorb into approved absorbent; place material into approved containers for disposal; do not wash to sewer or waterway.

SECTION 7 - HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Keep container closed when not in use; protect containers from abuse; protect from extreme temperatures. CAUTION - FLAMMABLE - keep away from all sources of ignition. "Empty" containers may contain residue which may form explosive vapors. Do not weld or cut near empty container that has not been professionally reconditioned. Use non-sparking tools when opening and closing containers. Maintain well ventilated work areas to minimize exposure when handling this material.

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

HAZARDOUS COMPONENTS	NIOSH				ACGIH			
	TWA ppm	TWA mg/m3	STEL ppm	STEL mg/m3	TWA ppm	TWA mg/m3	STEL ppm	STEL mg/m3
Kerosene (petroleum), hydrosulfurized	30				30			
Petroleum distillate, hydrotreated heavy paraffinic		10		5		10		5
Petroleum distillate, hydrotreated heavy paraffinic		10		5		10		5
Benzyl disulfide		not established				not established		

PERSONAL PROTECTION:

RESPIRATORY PROTECTION: None required while threshold limits are kept below maximum allowable concentrations; if TWA exceeds limits, NIOSH approved respirator must be worn. Refer to 29 CFR 1910.134 or European Standard EN 149 for complete regulations.

PROTECTIVE GLOVES: Neoprene, butyl or nitrile rubber gloves with cuffs.

EYE PROTECTION: Chemical safety goggles. Refer to 29 CFR 1910.133 or European Standard EN166.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Safety eyewash station nearby.

WORK / HYGIENIC PRACTICES: Practice safe workplace habits. Minimize body contact with this, as well as all chemicals in general.